

## Instruction of use



## Aclean 500

### General

Aclean 500 is a highly effective cleaner for all water resistant surfaces. Aclean 500 removes all types of soil such as oil, grease or wax.

Aclean 500 is free from sulphates, chlorides, nitrates, phosphates and any conservants.

### Application

Aclean 500 has to be sprayed on the cleaning surfaces. Upon completion, the surface is to be wiped of or rinsed with water.

### Work protection

Please note the hazard information on the product label and on the separate safety data sheet.

### Environmental protection

Used Aclean 500 solutions contain a varying amount of soil. Adhere to the instructions given by the authorities pertaining to surface and ground water protection.

### Disclaimer

With this revision all previous issues become invalid. The information is given to the best of our knowledge and belief and meet the experience gained in practice and in the laboratory up to the date of print. Nevertheless, they can only be considered as reference values without obligation, which have to be adapted to individual requirements. Due to the fact that the application of our products is beyond our control, our liability is limited to the perfect standard quality of the product at the time of delivery. Consequential damage can only be accepted if the assured properties of the product have been agreed to in writing prior to its use.



**Chemetall (Schweiz) AG, Silostrasse 7, CH-5606 Dintikon**  
Phone: +41(0)56 616 90 30 Fax: +41(0)56 616 90 40  
E-Mail: chemetall.schweiz@chemetall.com  
„A company of mg chemical group Dynamit Nobel“